



SECTION A-A

D2224 RAPPEL ANCHOR

NOTES:

- 1) MATERIAL: 7075-T73 (OR 7075-T7351/T73510/T73511) ALUMINUM BAR
PER AMS-QQ-A-200/11 OR AMS-QQ-A-225/9 (AMS 4124)
OR AMS-QQ-A-250/12 (AMS 4078)
OR 7075-T6 (OR T651/T6510/T6511/T62) ALUMINUM BAR
PER AMS-QQ-A-225/9 (OR AMS 4122/4123/4186/4187)
OR PER AMS-QQ-A-200/11
REF DART SPEC M7075T73B OR M7075T6B
- 2) FINISH: ANODIZE RED PER MIL-A-8625F TYPE I OR IB OR IC OR II OR IIB CLASS 2
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.010 TO 0.020 MAX
- 6) IDENTIFICATION: IDENTIFY PER QSI 044 6.1
- 7) WEIGHT: 0.27 lbs

RELEASED

2018 OCT 22
ECN 18-010

APPROVED

F	RE-FORMATTED TO CURRENT STANDARD; ADDED R0.031; REVISE DIMENSIONS; REF CIR18-122	RF	18.09.17
E	REVISE MATERIAL SPECIFICATIONS	RF	99.04.29
D	CHANGE TO T-SHAPE	DS	97.04.25
C	ADDED D2224-60	BW	96.06.17
B	D2227 WAS 2216	JB	95.04.11
A	NEW ISSUE	JB	94.03.10
REV.	DESCRIPTION	BY	DATE
DESIGN	DS	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	RF		
CHECKED	VS	DRAWING NO.	REV. F
MFG. APPR.	JFS	D2224	SHEET 1 OF 1
APPROVED	VS	TITLE	SCALE
DE APPR.	CP	RAPPEL ANCHOR	NTS
DATE	18.09.17	COPYRIGHT © 1994 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	